



APPLICATION

Use for modular design for OEM and custom project based designs. For Accent, Large Scale Signage, Architectural Surfaces, Indirect/Direct Lighting for cabinets and displays. Perfect for applications desiring a dynamic color changing affect. Recommended for retail, modern residential, hospitality and night life installations. Install by surface mount to any surface using screws or supplied doubled sided 3M Brand Tape. Belongs to V12 Series family.

ELECTRICAL

Power Input: Low voltage V12 power from Satellite /Data Supply

Power Input Data Connection: Proprietary 4-Pin Quick Connectors

Power Consumption: 3.4W

PHYSICAL

Environment: Dry location

Construction: Printed Circuit Board

L70 Life: 35,000 Hours

COLOR DETAILS

DirectDMX Color Control: DMX or Pre-Programmed through Satellite Power/Data Supply

LED Die Colors: Red (620-635nm) Blue (450-465nm)
Green (520-535nm) Neutral White (5000k)

Color Mixing: InternaMix Unified Color Mixing via 3-in-1 LED Source
Static Colors Available: All Std. Colors, Consult Factory

Wireless Bluetooth Control: Bluetooth control via wireless data enabler. Calls up standard colors or shows. One Bluetooth enabler per zone.

COMPATIBILITY

COMPATIBILITY:

MODULES:

SMPS08-14RGB
8" Square (14W)

SMPS12-14RGB
12" Square (14W)

SMPR03-4RGB
4" Round (5W)

SATELLITE DATA ENABLERS:

SDEV12RGB-60:
60W Data Enabler



SDEBT-24VRGBW-400

200W 4-Channel
Miniature Bluetooth
Enabler (Power Supply
Req'd) Dry Locations only